

36 HP ^{26.8} kW 5036 D



John Deere Promise
5 YEARS
WARRANTY*

— TECHNOLOGY LEADERSHIP —

Self Lubricated Rear Oiled Axle

- More performance • More life
- Less maintenance • Useful for all farming applications

*Conditions apply



Power Steering



Single piece hood
with lock



International Looks



Also available with
JBLink™

*Zindagi ka
Best Decision!™*



JOHN DEERE

Technical Specifications

ENGINE

Type	: John Deere 3029D, 36 HP (26.8 kW), 2100 RPM, 3 Cylinders, Coolant cooled with overflow reservoir, Naturally aspirated
Air filter	: Dry type, Dual element

TRANSMISSION

Clutch	: Single
Gear box	: 8 Forward + 4 Reverse, Collarshift
Speeds	: Forward 3.13 - 34.18 kmph Reverse 4.10 - 14.87 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

Maximum Lifting capacity	: 1600 kg
3 point linkage	: Category - II Automatic depth and draft control (ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type	: Independent, 6 Splines
Standard	: 540 @ 2100 ERPM

WHEELS AND TYRES

Front	: 6.0 X 16 (0.15 X 0.41 m), 8 PR
Rear	: 12.4 X 28 (0.31 X 0.71 m), 12 PR 13.6 X 28 (0.34 X 0.71 m), 12 PR (Optional)

FUEL TANK

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery,
40 Amp. alternator,
12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight	: 1760 kg
Wheel base	: 1970 mm
Overall length	: 3400 mm
Overall width	: 1780 mm
Ground clearance	: 0390 mm
Turning radius with brakes	: 2900 mm

ACCESSORIES*

- Ballast weights • Canopy • Canopy holder
- Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

- **JDLINK** (Alerts, Monitoring and Tracking System)
- Roll over protection structure (ROPS) with deluxe seat and seat belt
- Adjustable front axle

FEATURES

- Collarshift type gear box • Finger guard • Water separator
- PTO NSS • Digital hour meter • Underhood exhaust muffler
- Mobile charging point with holder • Hydraulic auxiliary pipe
- Planetary gear with straight axle

Note: All the options / features may not be available in a single variant.

36 HP ^{26.8} _{kw}
5036 D

Modern, technologically advanced,
powerful John Deere 3029D engine

- **Wet liner**
Long life and less maintenance
- **High torque reserve**
Ideal for heavy load applications
- **High torque across the operating speed range**
- **Rear oiled axle with metal face seal**

Multi-Utility Tractor



John Deere Genuine Parts

| Economical | Reliable |
| Easily available |



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City,
Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office. Sales & Service through John Deere authorized dealers only.



- Tractors • Implements
- Harvesters • Finance



JOHN DEERE

Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.