



More performance, More life. Less maintenance, Useful for all farming applications



Power steering



Single piece hood with lock





Technical Specifications

ENGINE

Type : John Deere 3029D, 41 HP (30.8kW),

2100 RPM, 3 Cylinders,

Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift Speeds : Forward 3.25 - 35.51 kmph

Reverse 4.27 - 15.45 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

Maximum Lifting

capacity : 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type :Independent, 6 Splines Standard :540 @ 2100 ERPM Standard :540 @ 1600 ERPM

(Optional, available along with standard PTO)

WHEELS AND TYRES

Front : 6.0 X 16 (0.15 X 0.41 m), 8 PR Rear

: 12.4 X 28 (0.31 X 0.71 m), 12 PR (Optional) : 13.6 X 28 (0.34 X 0.71 m), 12 PR

FUEL TANK

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. alternator

12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 1760 kg
Wheel base : 1970 mm
Overall length : 3400 mm
Overall width : 1780 mm
Ground clearance : 0390 mm
Turning radius with brakes : 2900 mm

ACCESSORIES*

• Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

Dual PTO

 Roll over protection structure (ROPS) with deluxe seat and seat belt

Adjustable front axle

Mechanical guick raise and lower (MQRL)

FEATURES

- Collarshift type qear box PTO NSS Water separator
- Digital Hour Meter Mobile Charging Point with Holder
- Underhood exhaust muffler Hydraulic auxiliary pipe
- Planetary Gear with Straight Axle Finger Guard

Note: All the options / features may not be available in a single variant.



Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner
 Long life and less maintenance

 High torque reserve Ideal for heavy load applications

High torque across the operating speed range

Rear oiled axle with metal face seal



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



Top Shaft Lubrication

John Deere Genuine Parts

I Economical I Reliable I Easily available I




John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.







• Harvesters • Finance

